



### PREMIUM PORTABLE UNITS

Comfee 'Premium Portable' air conditioning units are available in either 2.5kW or 3.5kW. The energy efficient units are easy to control via the MSmarthome APP. With a simple swipe, the units can be turned on/off and the appropriate mode and temperature selected.

#### VOICE AND APP CONTROL

All portable units can be controlled by the MSmartHome App and can be used with Alexa and Google Home voice commands.

#### ENERGY SAVING

The power consumption of the unit is equal to 0.5 W. This allows great energy savings.

#### SLEEP MODE FUNCTION

With a precise temperature control system, "sleep mode" creates an ideal climate in your room so you can wake up comfortable and fully refreshed.

#### EASY TO MOVE

The unit sits on easy glide castor wheels, making it easy to transport and move the unit into different rooms.

#### SELF EVAPORATING

The water collected is automatically evaporated, so there is no need to worry about emptying trays.

#### AUTOMATIC RESTART

In the event of a power failure, the unit restarts with the settings previously in use.

#### LED DISPLAY

The LED display shows the temperature of the unit and gives an indication of any errors, allowing for auto protection and self diagnosis.

#### 24 HOUR TIMER

Use the 24 Hour/7 Day timer via the APP to control the portable unit.

[COMFEE-UK.COM](http://COMFEE-UK.COM)



**3**  
YEAR  
WARRANTY

ENERGY  
RATING  
**A**




Timer

ECO timer



No Drain-Pipe  
Required



Easy to clean filter



Power cord tidy  
design



360° Castor Wheels



Voice Control



MSmartHome



**comfee'**  
*...is how I feel!*

### PREMIUM PORTABLE UNITS

MODEL			MPPFA1-09CRN7	MPPFB1-12CRN7
Power supply (Powered via 3 Pin Plug)		Ph-V-Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Cooling	Capacity	Btu/h	9000	12000
	Capacity	KW	2.5	3.5
	Input	W	1015	1350
	Current	A	4.5	5.9
	EER	W/W	2.6	2.6
	Energy Efficiency Class		A	A
Moisture Removal		L/h	2.3	3.189
Rated Input Consumption		W	1200	1600
Rated Current		A	6.4	8.3
Starting Current		A	20	25
Indoor Air Flow (Hi/Mi/Lo)		m3/h	380/350/304	400/360/320
Indoor Side Noise Level (Hi/Mi/Lo)		dB(A)	53.9/52.6/51.3	53/51/50
Sound Power Level (Hi)		dB(A)	65	63
Power Consumption in Standby Mode		W	0.5	0.5
Refrigerant Type	Type		R290	R290
	GWP		3	3
	Charged Quantity	kg	0.21	0.24
	CO2 Quantitiy	kg	0	0
Design Pressure		MPa	2.6/1.0	2.6/1.0
Plug Type			1.5x3/VDE	1.5x3/VDE
Control Type			Remote Control	Remote Control
Operation Temp (room temp)		°C	17-35	17-35
Dimension (W*D*H)		mm	435x342x720	458x373x775
Packaging (W*D*H)		mm	475x410x870	510x440x880
Net/Gross Weight		kg	26.31/32.67	31.2/34.6