

# Monoblock Air Conditioning System



## Model: KFR-28MB/LUX

The KFR-28MB/LUX is a Monoblock through-the-wall air conditioning system designed for efficient climate control without the need for an external unit. Its sleek, self-contained design makes it ideal for homes, offices, and commercial spaces where traditional split systems are impractical. This unit delivers reliable cooling and heating performance while maintaining a compact and stylish appearance.

Engineered for convenience, the KFR-28MB/LUX does not require an FGAS engineer for installation. The system includes a sealing strip to enhance insulation, reducing energy loss and maximizing efficiency. With easy-to-use controls and a commitment to environmental responsibility, this air conditioner offers a sustainable and effective solution for year-round comfort.

## Features

- Monoblock Design
- Cooling & Heating
- Wall-Mounted Installation
- Energy Efficient
- Sealing Strip for Insulation
- User-Friendly Controls
- Quiet Operation
- DIY Installation
- Environmentally Responsible



**NO FGAS Engineer  
Required For Installation**



## Specifications

Model Number	KFR-28MB/LUX
Cooling Capacity (BTU/H)	10,000
Heating Capacity (BTU/H)	9,000
Power Supply	220-240V/50Hz
EER	2.61
Rated Power Input (Cooling)	1050W
Rated Power Input (Heating)	850W
Rated Current Input (Cooling)	4.6A
Rated Current Input (Heating)	3.7A
Refrigerant Charge	R32
Noise Level (dB) (A)	53
Body Size (WxDxH)	965*200*615
Carton Size (WxDxH)	1026*246*760
Net Weight (Kg)	36
Gross Weight (Kg)	40
Indoor Operating Temp (°C)	7-35
Application Area (m <sup>2</sup> )	15-20
Control Type	Remote Control



**No Outside Unit Required**

Features

1. 4 in 1 operation system consists of Cool , heating , Dry and Fan functions
2. R32 Gas with low impact on global warming
3. DC inverter technology ,maximum comfort ,minimum consumption
4. Automatic Swing or Customizable flap position,to optimize air flow in the room
5. Ventilation speed :3+auto
6. Digital remote control with LCD screen
7. Programmable on/off 24H timer