

# Product specifications

Specifications	Units	KT 20
Capacity(30°C/80% RH)	l/24h	21
Air flow	m <sup>3</sup> /h	375
Operating temperature range	°C	5-35
Operating humidity range	% RH	30-90
Power consumption	W	380
Power supply	V/Hz	230/1ph/50
Refrigerant	type	R290
Sound level	dB(A)	60
Compressor	type	Rotary
Product size (l x w x h)	mm	360 x 330 x 490
Box size (l x w x h)	mm	410 x 430 x 570
Net/gross weight	kg	20/22
Pallet	pcs	18

# Product specifications

Specifications	Units	AD 935
Capacity (30°C/80% RH)/Power consumption	l/24h/W	34/610
Capacity (20°C/60% RH)/Power consumption	l/24h/W	16.5/450
Air flow (Stage 1/ Stage 2/ Night mode)	m <sup>3</sup> /h	300/420/300
Operating temperature range	°C	5-30
Operating humidity range	% RH	30-90
Max. power consumption	W	610
Power supply	V/Hz	230/50
Sound level	dB(A)	51
Condensate tank	l	8
Condensate drain	mm	15
Power cord	m	5
Refrigerant		R454C
Product size (h x w x d)	mm	860 x 391 x 508
Weight	kg	35.4

# Product specifications

Specifications	Units	AD 935
Capacity (30°C/80% RH)/Power consumption	l/24h/W	34/610
Capacity (20°C/60% RH)/Power consumption	l/24h/W	16.5/450
Air flow (Stage 1/ Stage 2/ Night mode)	m <sup>3</sup> /h	300/420/300
Operating temperature range	°C	5-30
Operating humidity range	% RH	30-90
Max. power consumption	W	610
Power supply	V/Hz	230/50
Sound level	dB(A)	51
Condensate tank	l	8
Condensate drain	mm	15
Power cord	m	5
Refrigerant		R454C
Product size (h x w x d)	mm	860 x 391 x 508
Weight	kg	35.4

# Product specifications

Specifications	Units	HF2
Inserted air filter		Each 1 pc. is included with the delivery: – prefilter G4 – HEPA-Filter H13 acc. EN1822 (Separation MPPS > 99.95%)
Max. air flow	m <sup>3</sup> /h	270
Control/operation		LED indicator for filter change and button for battery check
Product size (h x w x d)	mm	260 x 390 x 490
Weight	kg	6

# Product specifications

Specifications	Units	VT 2
Pump type		Robust sewage pump
Conveyor volume	m <sup>3</sup> /h	7
Max. conveyor height	m	5
Tank volume	l	20
Operating temperature range	°C	3-38
Power consumption	W	260
Power supply	V/Hz	230/1ph/50
Power cord	m	4.5m with plug, heavy-duty version, (H07-cable) with magnet-holder for plug
Protection class		IP44
Product size (h x w x d)	mm	507 x 390 x 490
Weight	kg	18

# Product specifications

Specifications	Units	VP 6
Blower type		Brushless high-performance turbine blower
Air flow (free blowing)	Speed:m <sup>2</sup> /m <sup>3</sup> /h	1/15/80 - 2/30/140 - 3/50/190 - 4/70/250
Excess pressure	mbar	270
Low pressure	mbar	220
Motor power	W	1,280
Operating temperature range	°C	0-38
Power supply	V/Hz	230/1ph/50
Sound level @ 3m	dB(A)	57
Power cord	m	4.5m with plug, heavy-duty version, (H07-cable) with magnet-holder for plug
Protection class		IP44
Product size (h x w x d)	mm	507 x 390 x 455
Weight	kg	15

# Product specifications

Specifications	Units	SD 2
Max. air flow	m <sup>3</sup> /h	220
Product size (h x w x d)	m	300 x 390 x 490
Weight	kg	6

Specifications	Units	TTR 300
Capacity (20°C/60% RH)	kg/h	0.7
Dry air range	m <sup>3</sup> /h	80 - 280
Dry air air volume nominal	m <sup>3</sup> /h	200
Available pressure	Pa	100
Regeneration air flow	m <sup>3</sup> /h	30
Available pressure	Pa	50
Operating temperature range	°C	-15 - +35
Operating humidity range	RH	0 - 100
Power supply	V/Hz	230/1ph/50-60
Power input total	kW	0.9
Power input heating	kW	0.85
Sound level @1m	dB(A)	61
Connections dry air outlet	Ømm	100
Connections humid air outlet	Ømm	50
Product size (l x w x h)	mm	355 x 310 x 355
Weight	kg	12



Specifications	Units	TTR 500 D
Capacity (20°C/60% RH)	kg/h	2.2
Dry air range	m <sup>3</sup> /h	180 - 550
Dry air air volume nominal	m <sup>3</sup> /h	480
Available pressure	Pa	150
Regeneration air flow	m <sup>3</sup> /h	80
Available pressure	Pa	80
Operating temperature range	°C	-15 - +35
Operating humidity range	% RH	0 - 100
Power supply	V/Hz	230/1ph/50-60
Power input total	kW	3.0
Power input heating	kW	2.7
Sound level @1m	dB(A)	74
Connections dry air outlet	Ømm	125
Connections humid air outlet	Ømm	80
Product size (l x w x h)	mm	443 x 400 x 452
Weight	kg	25

# Product specifications

Specifications	Units	VP 3
Blower type		Side channel blower
Air flow	m <sup>3</sup> /h	150 (free blowing)
<b>Max. pressure differential:</b>		
Vacuum	mbar	170
Pressure	mbar	190
Motor power	W	1,100
Operating temperature range	°C	0-38
Sound level	dB(A)	50
Power supply	V/Hz	230/1ph/50
Protection class		IP44
Product size (h x w x d)	mm	507 x 390 x 455
Weight	kg	26.5